

# Agricultural Tractor 4WD



New series: (45HP-60HP)



# RELIABLE



- Strengthen the rear axle, connect bridge, gearbox the safety factor of the whole machine can be increased by 25%.
- The use quality of the whole machine is improved, the tire adhesion is increased, the maximum traction force can be increased by 20%.
- Gearbox air tight test, to make sure gearbox not leakage.



# APPLICATION+

upland field



paddy field



orchard



garden



farmstead





# RANGE

- Power:45HP-60HP,4x4
- customized technical suit for your land.
- Shuttle shift (8+8) chassis, chassis is reliable. The whole machine structure compact, easy to operate. A variety of wheels are optional, the rear wheels are step-less and adjustable. Equipped with double-acting clutch, separate walking and working, farming range can be increased by 10%.





# ATTACHMENTS



Moldboard Plow



Disc Plow



Slasher



Harrow Plow



Ridging Plow



Ditcher/Trench



Rotary Tiller



Bar Mower



Forklift




Trailer



Reversible Plow



Backhoe



Rake



Potato Harvester



Potato Seeder/Planter



Boom Sprayer



Front Loader



Round Baler



Fertilizer



Ridger



Cultivator



Square Baler



Cut & Rake



Vegetable Planter/Seeder



Shovel



Corn Harvester



Corn Planter/Seeder



Subsoiler



Wheat Harvester



Wood Chipper



Disc Ridger



Auger/Drill



# TECHNICAL FEATURES

Model	EG-Four Wheel Tractor 454	EG-Four Wheel Tractor 504	EG-Four Wheel Tractor 554	EG-Four Wheel Tractor 604
Drive Type	4x4WD, Gear Transmission			
Gear Shift	8F+8R			
Clutch Type	Double-Acting			
Steering	Hydraulic			
Differential	Differential Lock			
Ground Clearance (mm)	390			
Hydraulic Suspension	3-Point Hitch			
PTO Shaft Type	Dependent, Clockwise, 6 Spline, 540/760rpm			
Fuel Consumption (g/kW*h)	≤251.6			
Engine Type	4 Cylinder, Water-Cooled, Diesel			
Rated Traction Force (kN)	10.50	13.00	14.70	15.50
Overall Dimension (LxWxH/mm)	3150x1360x2050	3150x1360x2050	3450x1380x2180	3450x1380x2180
Structural Weight (kg)	1530	2030	2200	2480
Wheelbase (mm) Adjustable	1690	1835	1910	2010
Tread (mm) Adjustable	1100/1200	1100/1200	1180/1460	1180/1460
Min.Turning Radius (m)	4.50	4.50	4.80	4.80
Tire Model (F/R)	6.50-16/11.2-24	6.50-16/11.2-24	6.50-16/11.2-24	6.50-16/11.2-24
12-Hour Rated Power (kW)	33.09 (45HP)	36.80 (50HP)	40.40 (55HP)	44.10 (60HP)
Rated Speed (rpm)	2300	2300	2300	2300
Displacement (L)	2.55	3.17	4.16	4.22

# FEATURE

1. Optional installation of a group of hydraulic output, can be configured with a variety of agricultural machinery and tools.
2. Optional forced up and down, double oil cylinder lifting, the maximum lifting force is greater than 1000Kg, lifting force increased by 20%.
3. Hydraulic power steering system, four-wheel drive models can equip full hydraulic steering, that means your steering will be more smooth and flexible, just enjoy your driving. Small turning radius: 2-wheel drive 3.4m, 4-wheel drive 4.2m.
4. The hydraulic pipe oil seal is imported, to preventing oil leakage.
5. Optional different famous brand engine.

# SERVICES

## Spare parts:

A complete range of original spare parts, guaranteed directly.

## Warranty:

A precise certainty for the customer's satisfaction: 2-year warranty.

## Assistance:

A team of specialists, well prepared and available to assure an efficient and resolving service.  
Agricultural machinery industry information and customer marketing assistance.

[www.pandatractor.com](http://www.pandatractor.com)  
[silvia@pandatractor.com](mailto:silvia@pandatractor.com)

[pandatractor.com](http://pandatractor.com)