

Micro Tractor		12HP	15HP	18HP	20HP
Engine Model		195	1100	1105	1110
Displacement		0.63	0.60	0.70	0.79
Dimension: (L×W×H/mm)		2140×990×1175	2140×990×1175	2140×990×1200	2140×990×1200
Fuel Efficiency		≤257gl/kw.hr	≤257gl/kw.hr	≤245gl/kw.hr	≤240.2gl/kw.hr
Working Weight (kg)		490	520	630	640
Type		1 Cylinder, 4-Stroke, Horizontal, Water-Cooled, Direct Injection, Diesel			
Cooling Mode		Condenser (Radiator)			
Compression Ratio		18:01			
Rated Speed		2400rpm			
Fuel Tank Capacity		8L			
Front Wheel Size		5.00-12			
Back Wheel Size		7.50-16			
Ground Clearance (>mm)		180			
Transmission Style		Belt Transmission			
Steering Style		Steering Wheel Power Steering System			
Brakes		Two Side Wheel Brake			
Starter		Electric Start/Hand Start			
Gear Style		(3+1)*2			
Wheel Track (mm) Adjustable		990-1280			
Rotary Tiller	Width	1000mm Adjustable			
	Blades Qty (pcs)	18-24 Pcs			
	Working Depth (mm)	150-250			
	Up & Down Control	Hydraulic System			