

<b>Belt Tractor</b>	<b>15HP</b>	<b>18HP</b>	<b>20HP</b>	<b>22HP</b>
Drive Type	4*2 WD, Belt Transmission			
Engine Type	Water-Cooled, 4-Stroke, Direct Injection, Diesel			
Starting System	Electrical Start			
Dimension (L*W*H/mm)	2500*1150*1800			
Wheel Base (mm) Adjustable	1330			
Wheel Tread F/R (mm)	900/960			
Gear Shift	6F+1R			
Clutch Type	Dry, Double Disc, Friction			
Tire F/R	500-12/950-16			
Steering	Mechanical Steering			
Brake	Toe Type			
Park Brake	Latch Pedal			
Hitch	3-Point Hitch			
Hydraulic Pump	Gear Pump			
Max. Lift Force (N)	≥3812			
Rear PTO	Rear Rectangle Spline, 6 Teeth, 540rpm			

<b>Belt Tractor</b>	<b>24HP</b>	<b>28HP</b>	<b>30HP</b>	<b>32HP</b>
Drive Type	4*2 WD, Belt Transmission			
Engine Type	Water-Cooled, 4-Stroke, Direct Injection, Diesel			
Starting System	Electrical Start			
Dimension (L*W*H/mm)	2500*1150*1800			
Wheel Base (mm) Adjustable	1400			
Wheel Tread F/R (mm)	6F+1R			
Gear Shift	Dry, Double Disc, Friction			
Clutch Type	600-14/950-20			
Tire F/R	Mechanical Steering			
Steering	Toe Type			
Brake	Latch Pedal			
Park Brake	3-Point Hitch			
Hitch	Gear Pump			
Hydraulic Pump	≥3812			
Max. Lift Force (N)	Rear Rectangle Spline, 6 Teeth, 540rpm			
Rear PTO	950/990	950/990	950/990	990/1000