

2WD Mini Tractor		120	160	180	200	220
12-Hour Rated Power (kW)		8.50 (12HP)	11.76 (16HP)	13.20 (18HP)	14.50 (20HP)	16.20 (22HP)
Drive Type		4x2WD, Gear Transmission				
Gear Shift		(3+1)x2				
Wheelbase (mm)		1380				
Tread (mm)		950/990				
Ground Clearance (mm)		275				
Min.Turning Radius (m)<		2.80				
Hydraulic Suspension		3-Point Hitch				
PTO Shaft Type		Dependent, Clockwise, 6 Spline, ϕ 35mm, 540rpm				
Tire Model		4.00-12/7.50-16				
Engine Type		Single Cylinder, Vertical, Water-Cooled, 4-Stroke, Diesel				
Fuel Consumption (g/kW*h)		\leq 251.6				
Rated Traction Force (kN)		3.10	3.50	3.70	4.00	4.60
Min. Operating Weight(kg)		805	805	810	810	930
Theoretical Max. Speed	Forward	25.27	25.27	29.37	29.37	31.76
	Reverse	8.66	8.66	10.05	10.05	11.21
Rated Speed (rpm)		2200	2400	2400	2400	2400
Displacement (L)		0.70	0.90	1.00	1.10	1.39