

<b>4WD Medium Tractor</b>	<b>45HP</b>	<b>50HP</b>	<b>55HP</b>	<b>60HP</b>
Drive Type	4x4WD, Gear Transmission			
Gear Shift	8F+8R			
Clutch Type	Double-Acting			
Steering	Hydraulic			
Differential	Differential Lock			
Ground Clearance (mm)	390			
Hydraulic Suspension	3-Point Hitch			
PTO Shaft Type	Dependent, Clockwise, 6 Spline, 540/760rpm			
Fuel Consumption (g/kW*h)	≤251.6			
Engine Type	4 Cylinder, Water-Cooled, Diesel			
Rated Traction Force (kN)	10.50	13.00	14.70	15.50
Structural Weight (kg)	1530	2030	2200	2480
Wheelbase (mm) Adjustable	1690	1835	1910	2010
Tread (mm) Adjustable	1100/1200	1100/1200	1180/1460	1180/1460
Min.Turning Radius (m)	4.50	4.50	4.80	4.80
Tire Model (F/R)	6.50-16/11.2-24			
12-Hour Rated Power (kW)	33.10	36.80	40.40	44.10
Rated Speed (rpm)	2300	2300	2300	2300
Displacement (L)	2.55	3.17	4.16	4.22