

4WD Mini Tractor		12HP	16HP	18HP
Drive Type		4x4WD, Gear Transmission		
Gear Shift		(3+1)x2		
Rated Traction Force (kN)		3.90	4.10	4.30
Overall Dimension (LxWxH/mm)		2285x1050x1665	2285x1050x1665	2285x1180x1720
Min.Operating Weight (kg)		805	805	810
Wheelbase (mm)		1400		
Tread (mm)		950/990		
Ground Clearance (mm)		275		
Min.Turning Radius (m)		3.50		
Max. Speed	Forward	25.27	25.27	29.37
	Reverse	8.66	8.66	10.05
Hydraulic Suspension		3-Point Hitch		
PTO Shaft Type		Dependent, Clockwise, 6 Spline, ϕ 35mm, 540rpm		
Tire Model		6.00-14/7.50-20	6.00-14/7.50-20	6.00-14/7.50-20
Engine Type		Single Cylinder, Vertical, Water-Cooled, 4-Stroke, Diesel		
12-Hour Rated Power (kW)		8.50	11.76	13.2
Rated Speed (rpm)		2400		
Fuel Consumption (g/kW*h)		\leq 251.6		
Displacement (L)		0.70	0.90	1.00

4WD Mini Tractor		20HP	22HP	24HP
Drive Type		4x4WD, Gear Transmission		
Gear Shift		(3+1)x2		
Rated Traction Force (kN)		4.70	5.60	6.20
Overall Dimension (LxWxH/mm)		2580x1200x1885	2580x1200x1885	2785x1250x1890
Min.Operating Weight (kg)		1100	1180	1200
Wheelbase (mm)		1400	1450	1450
Tread (mm)		950/990		990/1000
Ground Clearance (mm)		275		
Min.Turning Radius (m)		3.50	3.50	3.90
Max. Speed	Forward	29.37	31.76	32.66
	Reverse	10.05	11.21	12.27
Hydraulic Suspension		3-Point Hitch		
PTO Shaft Type		Dependent, Clockwise, 6 Spline, Φ 35mm, 540rpm		
Tire Model		6.00-14/7.50-20	6.00-14/7.50-20	6.00-14/9.50-20
Engine Type		Single Cylinder, Vertical, Water-Cooled, 4-Stroke, Diesel		Three Cylinder, Vertical, Water-Cooled, 4-Stroke, Diesel
12-Hour Rated Power (kW)		14.50	16.20	17.60
Rated Speed (rpm)		2400		
Fuel Consumption (g/kW*h)		\leq 251.6		
Displacement (L)		1.10	1.39	1.65